

# Outdoor Video Wall



- Outdoor LED Display Video Wall offered by us, is widely used for displaying different videos for outdoor purposes. This video wall is delivers one immersive, seamless image. This wall is modern, slim design allows the display to blend into any business environment.
- Pixel Pitch based Module Setup- P3, P4, P6, P8, P10 - customized size
- Video wall controller with Wireless, Wired connectivity with Content management software for easy upgradation-

## Our Prime Customers

# OUTDOOR LED DISPLAY VIDEO WALL

Technical Specification	Outdoor LED Display				
Model	ADR-P3	ADR-P4	ADR-P6	ADR-P8	ADR-P10
LED Type	SMD1415	SMD1921	SMD2727	SMD2727	SMD3535
Pixel Pitch	3mm	4mm	6mm	8mm	10mm
Module Resolution (W×H)	104 X 52=5408 Pixels	80X40=3200 Pixels	32X32=1024 Pixels	40X20=800 Pixels	32×16=215 Pixels
Module Dimension	320mm×160mm ×18.4mm	320mm×160m m×18mm	192mm×192m m×18mm	320mm×160m m×18.5mm	320mm×160m m
Module Weight	0.43±0.02kg	0.49±0.02kg	0.35±0.02kg	0.48±0.02kg	0.5kg
Single-dot Brightness Calibration	Support	Support	Support	Support	Support
White Balance Brightness	≥4500 CD/m <sup>2</sup>	≥5000 CD/m <sup>2</sup>	≥4500 CD/m <sup>2</sup>	≥4000 CD/m <sup>2</sup>	≥5500 CD/m <sup>2</sup>
Standard Color Temperature	6500K (1000K~ 9500K Adjustable )	6500K ( 1000K ~9500K Adjustable )	6500K ( 1000K ~9500K Adjustable )	6500K ( 1000K ~9500K Adjustable )	6500K ( 1000K ~9500K Adjustable )
Beam Angle (Hor/Ver°)	140° /140°	140°/120°	140°/140°	140°/140°	140°/140°
Contrast Ratio	3000 : 1	3000 : 1	3000 : 1	3000 : 1	3000 : 1
Input Power	879 W/m <sup>2</sup>	879W/m <sup>2</sup>	895W/m <sup>2</sup>	879W/m <sup>2</sup>	<950W/m <sup>2</sup>
Input Power	293W/m <sup>2</sup>	293W/m <sup>2</sup>	298W/m <sup>2</sup>	293W/m <sup>2</sup>	293W/m <sup>2</sup>
Power Voltage	AC90~132V/ AC186~264V, Frequency 47~63 (Hz)	AC90~132V/ AC186~264V Frequency 47- 63 (Hz)	AC90~132V/ AC186~264V Frequency 47-63 (Hz)	AC90~132V/ AC186~264V, Frequency 47~63 (Hz)	AC90~132V/ AC186~264V, Frequency 47~63 (Hz)
Frame Changing Frequency	≥60Hz	≥60Hz	≥60Hz	≥60Hz	≥60Hz
Drive Mode	Constant Current Drive / 13 Scan	Constant Current Drive / 10 Scan	Constant Current Drive / 8 Scan	Constant Current Drive / 5 Scan	Constant Current 1/2 scanning
Refresh Rate	≥1920Hz	≥1920Hz	≥1920Hz	≥1920Hz	≥1920Hz
Processing Depth	12~14 Bit	12~14 Bit	12~14 Bit	12~14 Bit	12~14 Bit
Video Support	2K HD, 4K UHD	2K HD, 4K UHD	2K HD, 4K UHD	2K HD, 4K UHD	2K HD, 4K UHD
Life Typical Value (HRS)	50000H	50000H	50000H	50000H	50000H
Working Temperature/ Humidity Range (°C/RH)	-20°C-50°C / 10%-65%RH	-20°C-50°C / 10%-65%RH	-20°C-50°C / 10%-65%RH	-20°C-50°C / 10%-65%RH	-20°C-50°C / 10%-65%RH
Storage Temperature / Humidity Range (°C/RH)	-10°C-30°C / 10%-60%RH	-10°C-30°C / 10%-60%RH	-10°C-30°C / 10%-60%RH	-10°C-30°C / 10%-60%RH	-10°C-30°C / 10%-60%RH