



Video Wall Controller



AdrTech

All the technology you need

All The Technology You Need

Specifications

Change History

Document Version	Release Date	Description
V1.8.0	2023-02-17	Added the description of the H_4xfiber sending card.
V1.7.0	2022-12-05	<ul style="list-style-type: none"> Added the descriptions of the H_4xDVI output card, H_4xHDMI output card and H_1xHDMI2.0 output card. Updated the decoding capability description of the H_2xRJ45 IP input card.
V1.6.0	2022-04-30	<ul style="list-style-type: none"> Added the section of Notes and Cautions. Updated the certifications. Added the description of the H_1xDP1.2 input card.
V1.5.2	2021-08-30	<ul style="list-style-type: none"> Added the description of the low latency function. Added the notes for use of the USB connectors and COM port. Updated the certifications.
V1.5.1	2021-06-10	Added the description of ordering or purchasing the optical module for the H_16xRJ45+2xfiber sending card.
V1.5.0	2021-04-30	Added the description of the H_1xHDMI2.0 input card.
V1.4.0	2021-03-31	<ul style="list-style-type: none"> Added the descriptions of the H_1x12G SDI inputcardandH_1xHDMI2.0 output card. Added the descriptions of the following new features: <ul style="list-style-type: none"> -XRs cenario control -DevicebackupandLED4Ksendingcardbackup
V1.3.1	2021-01-08	Added one HDMI cable to the product accessories.
V1.3.0	2020-11-30	<ul style="list-style-type: none"> Added the description of H_STDI/O card. Deleted the maximum screen quantity and added the maximum layer quantity in the specification table. Changed the maximum widths and heights supported by the dual-link DVI and HDMI input and output connectors.
V1.2.0	2020-09-04	<p>Added the descriptions of the following cards:</p> <ul style="list-style-type: none"> H_2xDP1.1inputcard H_20xRJ45sendingcard
V1.1.1	2020-08-20	Updated the maximum height supported by the H_16xRJ45+2xfiber sending card to 10240 pixels.
V1.1.0	2020-07-31	<ul style="list-style-type: none"> Added the descriptions of the following new functions: <ul style="list-style-type: none"> -Eye saver mode -3D function -Input source grouping and decimal frame rates -App control on the pad device Added the descriptions of the following input cards: <ul style="list-style-type: none"> -H_4x3G SDI input card -H_2xCVBS+2xVGA input card -H_4xVGA input card
V1.0.1	2020-06-02	Updated the description of the H_2xRJ45 IP input card.
V1.0.0	2020-05-15	First release

Introduction

The LED CONTROLLER is AdvanceTech India Pvt. Ltd. newest generation of video wall Controller, featuring excellent image quality and designed especially for fine-pitch LED screens. The LED CONTROLLER can work as splicing processors that integrate both video processing and video control capabilities, or work as pure splicing processors. The whole unit adopts a modular and plug-in design, and allows for flexible configuration and hot swapping of input and output cards. Thanks to excellent features and stable performance, the LED CONTROLLER can be widely used in a variety of applications, such as energy and power, judicial departments and prisons, military command, water conservancy and hydrology, meteorologic earthquake prediction, enterprise management, metallurgy of steel, banking and finance, national defense, public security traffic management, exhibitions and presentations, production scheduling, radio and television, educational and scientific research, as well as stage rental applications.

Based on the powerful hardware FPGA system architecture, with a modular and plug-in design, the LED CONTROLLER features a stable and highly efficient pure hardware architecture, and provides a variety of connector modules for flexible and personalized configuration, allowing for easy maintenance and low failure rate. The LED CONTROLLER provides the industry-standard input connectors, including HDMI, DVI, DP, VGA, CVBS, SDI and IP, and supports 10-bit video source input and processing, as well as 4K high-definition inputs and outputs. The LED CONTROLLER also provides two kinds of LED 4K sending cards, allowing for the backup between the OPT ports and Ethernet ports as well as ultra-long distance transmission. Moreover, the LED CONTROLLER supports multi-screen and multi-layer management, input and output EDID management and monitoring, input source renaming, BKG and OSD settings and more, bringing you a rich image construction experience.

In addition, the LED CONTROLLER adopts the B/S architecture and supports cross-platform, cross-system access and control without the need to install an application program. On a Windows, Mac, iOS, Android or Linux platform, online collaboration of multiple users is supported and the response speed is very fast, which greatly improves on-site setup efficiency. What's more, the LED CONTROLLER supports online firmware update, allowing for easy hardware update on a PC.

Certifications

CE, UKCA, FCC, IC, CB, NOM, RCM, KC, CMIM

If the product does not have the relevant certifications required by the countries or regions where it is to be sold, please contact AdvanceTech India Pvt. Ltd. to confirm or address the problem. Otherwise, the customer shall be responsible for the legal risks caused or AdvanceTech India Pvt. Ltd has the right to claim compensation.

Features

Modular and plug-in design, free combination at your will

- Three kinds of LED 4K sending cards
 - H_20xRJ45 sending card loads upto 13,000,000 pixels.
 - H_16xRJ45+2xfiber sending card loads up to 10, 400,000 pixels and provides two OPT ports that copy the outputs on Ethernet ports.
 - H_4xfiber sending card loads up to 20,800,000 pixels and supports three working modes, including independent, copy and backup.
- Multi-capacity configuration on a single card slot
 - 4x2K×1K@60Hz
 - 2x4K×1K@60Hz
 - 1x4K×2K@60Hz
- Simple screen configuration using a single card and connector
- Online status monitoring of all input and output cards
- Hot-swappable input and output cards
- H_2xRJ45 IP input card supports upto 512 IP camera inputs and input mosaic.
- Auto decryption of HDCP-encrypted sources
- Decimal frame rates supported
- HDR10 and HLG processing

Multi-screen management for centralized control

- Each screen can have its own output resolution.
- Output mosaic
 - Adopts the frame synchronization technology, which ensures all the output connectors output the image synchronously, and the image is Complete and played smoothly, without any stuck, frame loss, tearing or piecing.
- Irregular screen configuration
 - Supports irregular rectangle mosaic without any limitations

- Input source grouping management
- Eye saver mode
- Display the image in a warmer but less bright way to relieve eye strain.
- LCD bezel compensation

Diverse display possibilities for flexible configuration

- Multi-layer display
A single card supports 16x2K layers, 8xDL layers or 4x 4K layers.
All layers support cross-connector output and the layer quantity is not reduced for cross-connector output.
- High-definition scrolling text
Customize the scrolling text content, such as slogans or notification messages, and set the text style, scrolling direction and speed.
- Upto 2,000 presets
Fade effect and seamless witching supported, less than 60ms preset switching duration
- Scheduled play back of preset playlist
Set whether to add the presets to playlist, which is ideal for monitoring, exhibitions, presentations, and other applications.
- OSD settings on a single screen and adjustable OSD transparency
- BKG settings
BKG images do not occupy the layer resources.
The max. Width and height of a BKG image is up to 15K and 8K respectively.
- Channel logo management
Set a text or image logo for identifying the input source.
- Input source cropping and renaming after cropping
Crop any input source image and form a new input source after cropping.
- HDR and 10-bit video processing, allowing for a more exquisite and clear image
- Color adjustment
Output connector color and screen color adjustable, including the brightness, contrast, saturation, hue and Gamma
- XRs cenario control
- 3D function
Work with AdvanceTech's 3D emitter–EMT200 to enjoys the 3D visual effect.
- Low latency
Reduce the latency from the input source to the receiving card to as low as 1 frame.

Status monitoring for better stability and reliability

- Self-test for fault detection
- Auto monitoring and alarms
Supports hardware monitoring, such as fan rotation speed, module temperature and voltage, running status, and sends fault alarms if necessary.
- Backup design
 - Backup between devices
 - Backup between LED 4K sending cards

Appearance

Front Panel




*The picture shown is for illustration purpose only. Actual product may vary due to product enhancement.

Notes:

- This product can only be placed horizontally. Do not mount vertically or upside-down.
- The product can be mounted in a standard 19-inch rack capable of withstanding at least four times the total weight of the mounted equipment. Four M5 screws should be used to fix the product.

Name	Description
LCD screen	Displays the device status and monitoring information.

Rear Panel








*The picture shown is for illustration purpose only. Actual product may vary due to product enhancement.





Notes:




- The silkscreen marking "I-x" or "I/x" indicates the slot is dedicated to the input card."I" stands for input and "x" stands for the slot number. For example, "I-1" indicates this slot is the 1st input slot and for installing an input card only.
- The silkscreen marking "O-x" or "O/x" indicates the slot is dedicated to the output card."O" stands for output and "x" stands for the slot number. For example, "O-10" indicates this slot is the 10th output slot and for installing an output card only.
- The silkscreen marking " $\frac{I-x}{MVR}$ " indicates the slot can accept an input card or preview card.



Input Card	
H_4xDVI input card	<p>Support for single link and dual link input modes, and 10-bit input source HDCP 1.4 compliant Does not support interlaced signal input.</p> <ul style="list-style-type: none"> • Single link mode:



	<ul style="list-style-type: none"> -Four DVI connectors are all used for input. -Each connector supports the maximum resolution of 2048×1152 @60Hz and the minimum resolution of 800×600@60Hz. -Custom resolutions: Max. width: 2560 pixels (2560×972@60Hz) Max.height:2560pixels(884×2560@60Hz) • Dual link mode: <ul style="list-style-type: none"> -Connectors 2 and 4 are used for input, and connectors 1 and 3 are unavailable. -Each connector supports the maximum resolution of 3840×1080@60Hz and the minimum resolution of 800×600@60Hz. -Custom resolutions: Max. width: 3840 pixels (3840×1124@60Hz) Max.height:4095pixels(1014×4095@60Hz) <p>Status LEDs:</p> <ul style="list-style-type: none"> • On: The input source is accessed normally. • Off: No input source is accessed or the input source is abnormal.
H_4xHDMI input card	 <p>Support for 10-bit input source Does not support interlaced signal input.</p> <p>ForHDMI1.3inputs:</p> <ul style="list-style-type: none"> • Four connectors are all used for input. • Each connector supports the maximum resolution of 2048×1152@60Hz, and the minimum resolution of 800×600@60Hz. • Custom resolutions: Max.width:2560pixels(2560×972@60Hz) Max.height:2560pixels(884×2560@60Hz) • HDCP 1.4 compliant <p>For HDMI 1.4 inputs:</p> <ul style="list-style-type: none"> • Two HDMI 1.4 connectors are used for input, but two HDMI 1.3 connectors are unavailable. • Each connector supports the maximum resolution of 3840×1080@60Hz. • Custom resolutions: Max. width: 3840 pixels (3840×1124@60Hz) Max.height:4095pixels(1014×4095@60Hz) • HDCP1.4compliant <p>Status LEDs:</p> <ul style="list-style-type: none"> • On: The input source is accessed normally. • Off: No input source is accessed or the input source is abnormal.
H_1 x HDMI 2.0+1x DP1.2 Input card	 <p>Only one connector can be used each time.</p> <p>Set to use which connect. The default option is HDMI 2.0 connector. Does not support interlaced signal input.</p>



	<ul style="list-style-type: none"> • 1xHDMI 2.0 <ul style="list-style-type: none"> -Backward compatible with HDMI 1.4 and HDMI 1.3 -Supports the maximum resolution of 3840×2160@60Hz. -HDCP 2.2 compliant -Custom resolutions: <ul style="list-style-type: none"> Max. width: 4092 pixels (4092×2261@60Hz) Max.height:4095pixels(2188×4095@60Hz) • 1xDP1.2 <ul style="list-style-type: none"> -Backward compatible with DP 1.1 -Supports the maximum resolution of 4096×2160@60Hz or 8192×1080@60Hz. -HDCP 2.2 compliant -Custom resolutions: <ul style="list-style-type: none"> Max. width: 8192 pixels (8192×1146@60Hz) Max.height:4095pixels(2188×4095@60Hz) <p>Status LEDs:</p> <ul style="list-style-type: none"> • On: The input source is accessed normally. • Off: No input source is accessed or the input source is abnormal.
H_2xRJ45IP input card	 <p>2x RJ45 Gigabit Ethernet ports</p> <p>Support for interlaced signal input</p> <ul style="list-style-type: none"> • Supported protocols: RTSP, GB28181 and ONVIF • Supported coding formats: H.264 and H.265 • Single card decoding capability: <ul style="list-style-type: none"> -4x 800W -8x 400W -16x2 00W • DHCP compliant
H_4x3GSDI input card	 <p>4x 3G-SDI</p> <ul style="list-style-type: none"> • Backward compatible with HD-SDI and SD-SDI • Supports ST-424 (3G), ST-292 (HD) and SMPTE 259 SD. • Each connector supports the maximum resolution of 1920×1080@60Hz. • Supports 1080i/576i/480i de-interlacing processing. <p>Status LEDs:</p> <ul style="list-style-type: none"> • On: The input source is accessed normally. • Off: No input source is accessed or the input source is abnormal.
H_2xCVBS+2xVGA Input card	 <p>2x VGA</p> <ul style="list-style-type: none"> • Each connector supports the maximum resolution of 1920×1200@60Hz. <p>2x CVBS</p> <ul style="list-style-type: none"> • Supports PAL and NTSC.



	<p>Status LEDs:</p> <ul style="list-style-type: none"> ● On: The input source is accessed normally. ● Off: No input source is accessed or the input source is abnormal.
H_4xVGA input card	 <p>4x VGA</p> <ul style="list-style-type: none"> ● Each connector supports the maximum resolution of 1920×1200@60Hz. <p>Status LEDs:</p> <ul style="list-style-type: none"> ● On: The input source is accessed normally. ● Off: No input source is accessed or the input source is abnormal.
H_2xDP1.1 input card	 <p>2x DP1.1</p> <ul style="list-style-type: none"> ● Each connector supports the maximum resolution of 3840×1080@60Hz or 3840×2160@30Hz. ● Custom resolutions: <ul style="list-style-type: none"> –Max. width:3840pixels(3840×1124@60Hz) –Max.height:4095pixels(1014×4095@60Hz) ● Supports 8-bit and 10-bit inputs. ● Does not support interlaced signal input. ● HDCP 1.3 compliant <p>Status LEDs:</p> <ul style="list-style-type: none"> ● On: The input source is accessed normally. ● Off: No input source is accessed or the input source is abnormal.
H_1xDP1.2 input card	 <p>1x DP 1.2</p> <ul style="list-style-type: none"> ● Backward compatible with DP1.1 ● Each connector supports the maximum resolution of 4096×2160@60Hz or 8192×1080@60Hz. ● Custom resolutions: <ul style="list-style-type: none"> –Max. width:8192 pixels (8192×1146@60Hz) –Max. height:4095 pixels (2188×4095@60Hz) ● HDCP 2.2 compliant <p>Status LEDs:</p> <ul style="list-style-type: none"> ● On: The input source is accessed normally. ● Off: No input source is accessed or the input source is abnormal.
H_1x12GSDI input card	 <ul style="list-style-type: none"> ● 1x 12 G-SDI IN <ul style="list-style-type: none"> –Backward compatible with 6G-SDI, 3G-SDI, HD-SDI and SD-SDI –Supports ST-2082-1(12G), ST-2081-1(6G), ST-424(3G), ST-292(HD) and SMPTE 259 SD. –Each connector supports the maximum resolution of 4096×2160 @60Hz.

	<ul style="list-style-type: none"> -Supports 1080i/576i/480i de-interlacing processing. -Does not support input resolution and bit depth settings. • 1x12G-SDI LOOP <ul style="list-style-type: none"> Loop out the 12G-SDI signal. • Status LEDs: <ul style="list-style-type: none"> -On: The input or loop output is connected normally. -Off: No input or loop output is connected or the input or loop output is abnormal. 																																								
<p>H_1xHDMI2.0 input card</p>	 <p>1x HDMI 2.0</p> <ul style="list-style-type: none"> • Backward compatible with HDMI1.4 and HDMI 1.3 • Each connector supports the maximum resolution of 3840×2160@60Hz. • HDCP 2.2 compliant • Custom resolutions: <ul style="list-style-type: none"> -Max. width:4092 pixels (4092×2261@60Hz) -Max. height:4095 pixels (2188×4095@60Hz) • Status LEDs: <ul style="list-style-type: none"> -On: The input source is accessed normally. -Off: No input source is accessed or the input source is abnormal. 																																								
<p>H_STDI/O card</p>	 <p>This card can be installed into the input card slots.</p> <ul style="list-style-type: none"> • 2x COM <p>Programmable RS422/RS485/RS232 ports that are used to control the devices that adopt RS422/RS485/RS232 protocol</p> <ul style="list-style-type: none"> -COM port pins are shown as below:  <ul style="list-style-type: none"> -Pin wirings are shown as below: <table border="1" data-bbox="604 1354 1153 1591"> <thead> <tr> <th>PIN</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> <th>5</th> <th>6</th> <th>7</th> <th>8</th> <th>9</th> </tr> </thead> <tbody> <tr> <td>RS-232</td> <td colspan="2">RXD</td> <td colspan="2">TXD</td> <td colspan="2">GND</td> <td colspan="3"></td> </tr> <tr> <td>RS-422</td> <td>RXD-</td> <td colspan="2">TXD+</td> <td>GND</td> <td>RXD+</td> <td colspan="2">TXD-</td> <td colspan="2"></td> </tr> <tr> <td>RS-485</td> <td colspan="4"></td> <td>A</td> <td colspan="4">B</td> </tr> </tbody> </table> • 1x ETHERNET <ul style="list-style-type: none"> -Control the device that is connected to this card. -10/100Mbps self-adaptive -TCP/IP protocol and UDP/IP protocol supported • 3x I/O <ul style="list-style-type: none"> -Trigger the execution of the function requirements via programming. -Input and output modes supported -Pins 1, 2 and 3 can be set to either the input or output, and pin G is the common grounding pin for pins 1, 2 and 3. 	PIN	1	2	3	4	5	6	7	8	9	RS-232	RXD		TXD		GND					RS-422	RXD-	TXD+		GND	RXD+	TXD-				RS-485					A	B			
PIN	1	2	3	4	5	6	7	8	9																																
RS-232	RXD		TXD		GND																																				
RS-422	RXD-	TXD+		GND	RXD+	TXD-																																			
RS-485					A	B																																			


	<ul style="list-style-type: none"> • 3x RELAYOUT <ul style="list-style-type: none"> -Connect to the relay to control the power on and off of the connected device. -Voltage:30VDC, current:3A at maximum -Six pins are divided into three groups, which can be connected or disconnected via programming. • 3x IROUT <ul style="list-style-type: none"> -Programmable infrared control supported -Pins1, 2 and 3 are used for infrared emission, and pin G is the common grounding pin for pins 1, 2 and 3.
Output Card	
H_4x DVI output card	 <p>4x SL-DVI</p> <p>Support for single output and dual link output</p> <ul style="list-style-type: none"> • Single link output: <ul style="list-style-type: none"> -Four connectors are all available for output. -Each connector supports the maximum resolution of 2048×1152@60Hz. -Custom resolutions: <ul style="list-style-type: none"> Max. width: 2560 pixels (2560×972@60Hz) Max.height:2560 pixels (884×2560@60Hz) -Supports 8-bit RGB4:4:4/YCbCr 4:4:4/YCbCr 4:2:2 output. -Supports 10-bit YCbCr 4:4:4 output. • Dual link output: <ul style="list-style-type: none"> -Connectors 2 and 4 are available for output. Connector 1 copies the output on connector 2, and connector 3 copies the output on connector 4. -Adopts HDMI 1.4 protocol. -Each connector supports the maximum resolution of 4096×2160@30Hz/3840×1080@60Hz. -Custom resolutions: <ul style="list-style-type: none"> Max. width: 4096 pixels (4096×1124@60Hz) Max.height:4096pixels(1014×4096@60Hz) -Supports 8-bit RGB4:4:4/YCbCr 4:4:4/YCbCr 4:2:2output. -Supports 10-bit YCbCr 4:4:4output. <p>Status LEDs:</p> <ul style="list-style-type: none"> • On: The output connector is connected normally. • Off: The output connector is not connected.
H_4x HDMI output card	 <p>4x HDMI 1.4</p> <p>Support for single output and dual link output</p> <ul style="list-style-type: none"> • Single link output: <ul style="list-style-type: none"> -Four connectors are all available for output. -Each connector supports the maximum resolutionof2048×1152@60Hz. -Custom resolutions: <ul style="list-style-type: none"> Max. width: 2560 pixels (2560×972@60Hz) Max.height:2560 pixels(884×2560@60Hz)

	<ul style="list-style-type: none"> -Supports 8-bit RGB 4:4:4/YCbCr 4:4:4/YCbCr 4:2:2output. -Supports10-bitRGB4:4:4/YCbCr4:4:4output. • Dual link output: <ul style="list-style-type: none"> -Connectors 2 and 4 are available for output. <ul style="list-style-type: none"> Connector 1 copies the output on connector 2, and connector 3 copies the output on connector 4. -Each connector supports the maximum resolution of 4096×2160@30Hz/3840×1080@60Hz. -Custom resolutions: <ul style="list-style-type: none"> Max. width: 4096 pixels (4096×1124@60Hz) Max.height:4096 pixels(1014×4096@60Hz) -Supports 8-bit RGB 4:4:4/YCbCr 4:4:4/YCbCr 4:2:2output. -Supports 10-bit RGB 4:4:4/YCbCr 4:4:4output. <p>Status LEDs:</p> <ul style="list-style-type: none"> • On: The output connector is connected normally. • Off: The output connector is not connected.
H_1x HDMI 2.0 output card	 <ul style="list-style-type: none"> • 2x HDMI 2.0 <ul style="list-style-type: none"> -Connector 2copies the output on connector 1. -The connector supports the maximum resolution of 8192×1080@60Hz/4096×2160@60Hz. -Custom resolutions: <ul style="list-style-type: none"> Max. width: 8192 pixels (8192×1146@60Hz) Max.height:7680 pixels(1092×7680@60Hz) -Supports 8-bit or1 0-bit RGB 4:4:4/YCbCr 4:4:4/YCbCr 4:2:2output. • Status LEDs: <ul style="list-style-type: none"> -On: The output connector is connected normally. -Off: The output connector is not connected.
H_16xRJ45+2xfiber sending card	 <p>LED 4K sending card can load upto10, 400,000 pixels (max. width:10,240 pixels, max. height: 10,240 pixels).</p> <p>This card occupies two slots.</p> <ul style="list-style-type: none"> • 16xRJ45 Gigabit Ethernet outputs <ul style="list-style-type: none"> -Bit depth:8-bit <ul style="list-style-type: none"> A single Ethernet port loads upto 650,000 pixels. -Bitdepth:10-bit <ul style="list-style-type: none"> A single Ethernet port loads upto 320,000 pixels. -Backup between Ethernet ports • 2x OPT outputs <ul style="list-style-type: none"> -Support both SMF and MMF transmission. -OPT 1 copies and outputs the data on Ethernet ports 1–8. -OPT 2 copies and outputs the data on Ethernet ports 9–16.

	<p>Note:</p> <p>For the optical module connected to the OPT port, you need to order or purchase separately.</p>
<p>H_20xRJ45 sending card</p>	 <p>LED 4K sending card can load upto13, 000,000 pixels(max. width:10,752 pixels, max. height: 10,752 pixels).</p> <p>This card occupies two slots.</p> <ul style="list-style-type: none"> • 20xRJ45 Gigabit Ethernet outputs <ul style="list-style-type: none"> -Bit depth:8-bit A single Ethernet port loads upto 650,000 pixels. -Bitdepth:10-bit A single Ethernet port loads upto 320,000 pixels. • Backup between Ethernet ports
<p>H_4xfiber sending card</p>	 <p>4x10GOPT ports</p> <p>This card can load up to 20,800,000 pixels (max. width: 16,384 pixels, max. height:16,384 pixels)</p> <ul style="list-style-type: none"> • Independent, copy and backup modes are supported. • SM and MM optical modules are both supported, with a transmission distance of up to 10 km. • Supports 8-bit and 10-bit outputs. • The optical modules support SFP+ encapsulation. The supported module specifications include the followings: <ul style="list-style-type: none"> -10G SFP+ SR optical module -10G SFP+ LRM optical module -10G SFP+ LR optical module -10G SFP+ ER optical module -10G SFP+ ZR optical module -SFP+ CWDM optical module -SFP+ DWDM optical module -SFP+ BIDI optical module <p>Independent</p> <p>Four OPT ports are all used for output and have the same loading capacity. The loading capacity of one port is equal to that of 8 Ethernet ports.</p> <p>Copy</p> <p>OPT 1 and OPT 2 are used for main output. OPT 3 copies the output on OPT 1, while OPT 4 copies the output on OPT 2.</p> <p>Backup</p> <p>OPT 1 and OPT 2 are used for main output. OPT 3 serves as the backup of OPT 1, while OPT 4 serves as the backup of OPT 2.</p> <p>Note:</p> <p>Four10G SFP+ LR optical modules are included with the card and are already installed into the OPT ports.</p>

<p>H_2xRJ45+1xHDMI1.3 Preview card</p>	 <ul style="list-style-type: none"> • 2xRJ45 Gigabit Ethernet outputs Connect to the network for monitoring the inputs and outputs. • 1x HDMI 1.3 Connect to a monitor for displaying the monitoring information.
H_Control Card	
	
<p>GENLOCK</p>	<p>Supports bi-level and tri-level.</p> <ul style="list-style-type: none"> • IN: Accept the Gen lock signal • LOOP: Loop the Gen lock signal.
<p>ETHERNET</p>	<p>A Gigabit Ethernet port</p> <ul style="list-style-type: none"> • Connect to the control PC for communication. • Connect to the router, switch or PC.
<p>USB1 & USB2</p>	<p>2x USB 2.0</p> <ul style="list-style-type: none"> • Update the device program. • Import or export the device configuration parameters. <p>Note:</p> <p style="padding-left: 20px;">The USB connectors cannot provide power for the connected devices.</p>
<p>COM</p>	<p>A serial port that adopts RS232 serial protocol</p> <p>Support for central control system</p> <ul style="list-style-type: none"> • IN: Accept the signal from the central control system. • OUT: Loop the signal. <p>Note:</p> <p style="padding-left: 20px;">The COM port cannot be connected to the network (router or switch) or LED cabinet (receiving card).</p>
<p>Powers witch</p>	<ul style="list-style-type: none"> • -/ON: Power on the device. • O/OFF: Power off the device.

Applications



Specifications

Model		LED CONTROLLER
Rack Unit		2U
Max. Input Cards		4
Max. Input Channels		16
Max. Output Cards		2
Max. Output Channels		8
Max. Loading Capacity	LED 4K sending card	26 million pixels
	H_4x fiber sending card	41.6 million pixels
Max. Layers		32
Electrical Specifications	Power connector	100–240V~,50/60Hz, 4.0A
	Power consumption	210W
Operating Environment	Temperature	0°C to 45°C
	Humidity	0% RH to 80% RH, non-condensing
Storage Environment	Temperature	–10°C to +60°C
	Humidity	0% RH to 95% RH, non-condensing
Physical Specifications	Dimensions	482.6 mm × 529.8 mm × 88.1 mm
	Net weight	11kg (chassis)
	Gross weight	12.2 kg (chassis)
Noise Level (typical at 25°C /77°F)		<45 dB (A)
Packing Information	Packing box	660 mm × 570 mm × 210 mm
	Accessories	<ul style="list-style-type: none"> 1x Power cord 1x RJ45 Ethernet cable 1x Grounding cable 1x HDMI cable 1x Quick Start Guide 1x Certificate of Approval 1x Safety Manual 1x Custom Letter

Video Source Features

Input Connector	Color Depth		Max. Input Resolution
HDMI 2.0	8-bit	RGB 4:4:4	4096×2160@60Hz
		YCbCr 4:4:4	8192×1080@60Hz
		YCbCr 4:2:2	
		YCbCr 4:2:0	4096×2160@60Hz
	10-bit	RGB 4:4:4	4096×2160@30Hz
		YCbCr 4:4:4	4096×1080@60Hz
		YCbCr 4:2:2	4096×2160@60Hz
		YCbCr 4:2:0	
	12-bit	RGB 4:4:4	4096×2160@30Hz
		YCbCr 4:4:4	4096×1080@60Hz
		YCbCr 4:2:2	4096×2160@60Hz
		YCbCr 4:2:0	
DP 1.2	8-bit	RGB 4:4:4	4096×2160@60Hz
		YCbCr 4:4:4	8192×1080@60Hz
		YCbCr 4:2:2	
		YCbCr 4:2:0	Not supported
	10-bit	RGB 4:4:4	4096×2160@30Hz
		YCbCr 4:4:4	4096×1080@60Hz
		YCbCr 4:2:2	4096×2160@60Hz
		YCbCr 4:2:0	Not supported
	12-bit	RGB 4:4:4	4096×2160@30Hz
		YCbCr 4:4:4	4096×1080@60Hz
		YCbCr 4:2:2	4096×2160@60Hz
		YCbCr 4:2:0	Not supported
HDMI 1.4 DP 1.1	8-bit	RGB 4:4:4	4096×1080@60Hz
		YCbCr 4:4:4	
		YCbCr 4:2:2	
		YCbCr 4:2:0	Not supported
	10-bit	RGB 4:4:4	2048×1152@60Hz

Input Connector	Color Depth		Max. Input Resolution
		YCbCr 4:4:4	
		YCbCr 4:2:2	4096×1080@60Hz
		YCbCr 4:2:0	Not supported
	12-bit	RGB 4:4:4	2048×1152@60Hz
		YCbCr 4:4:4	
		YCbCr 4:2:2	4096×1080@60Hz
		YCbCr 4:2:0	Not supported
	HDMI 1.3	8-bit	RGB 4:4:4
YCbCr 4:4:4			
YCbCr 4:2:2			
YCbCr 4:2:0			Not supported
10-bit		RGB 4:4:4	2048×1152@60Hz
		YCbCr 4:4:4	
		YCbCr 4:2:2	
		YCbCr 4:2:0	Not supported
12-bit		RGB 4:4:4	2048×1152@60Hz
		YCbCr 4:4:4	
		YCbCr4:2:2	
		YCbCr 4:2:0	Not supported
SL-DVI	8-bit	RGB 4:4:4	2048×1152@60Hz
DL-DVI	8-bit	RGB 4:4:4	3840×1080@60Hz
VGA CVBS	-	RGB 4:4:4	1920×1080@60Hz
3G-SDI	<ul style="list-style-type: none"> • Supports upto 1920×1080@60Hz video inputs. • Input resolution and bit depth settings are not allowed. • Supports ST-424(3G) and ST-292 (HD). 		
12G-SDI	<ul style="list-style-type: none"> • Supports upto 4096×2160@60Hz video inputs. • Input resolution and bit depth settings are not allowed. • Supports ST-2082-1(12G), ST-2081-1(6G), ST-424(3G) and ST-292(HD). 		

Notes and Cautions

Notes For Battery

- The battery is not intended to be replaced.
- Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery can result in an explosion.
- Leaving a battery in a next extremely high temperature surrounding environment can result in an explosion or the leakage of flammable liquid or gas.
- A battery subjected to extremely low air pressure may result in an explosion or the leakage of flammable liquid or gas.

Notes for Installation

When the product needs to be installed on the rack, 8 screws at least M5*8 should be used to fix it. The rack for installation shall bear at least four times the total weight of the mounted equipment.

- Elevated Operating Ambient - If installed in a closed or multi-unit rack assembly, the operating ambient temperature of the rack environment may be greater than room ambient. Therefore, consideration should be given to installing the equipment in an environment compatible with the maximum ambient temperature (T_{ma}) specified by the manufacturer.
- Reduced Air Flow – Installation of the equipment in a rack should be such that the amount of air flow required for safe operation of the equipment is not compromised.
- Mechanical Loading –Mounting of the equipment in the rack should be such that a hazardous condition is not achieved due to uneven mechanical loading.
- Circuit Overloading –Consideration should be given to the connection of the equipment to the supply circuit and the effect that overloading of the circuits might have on over current protection and supply wiring. Appropriate consideration of equipment nameplate ratings should be used when addressing this concern.
- Reliable Earthing –Reliable earthing of rack-mounted equipment should be maintained. Particular attention should be given to supply connections other than direct connections to the branch circuit (e.g. use of power strips).

FCC Caution

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:(1)This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Others

- This is Class A product. In a domestic environment, this product may cause radio interference in which case the user may be required to take adequate measures.
- Please read the specifications thoroughly and use the product in accordance with the requirements. If you have any questions about the specifications, please contact us immediately. If you use the product improperly, not following the requirements, or for illegal purposes, you shall be solely responsible for any consequences arising there from.